

Rox700 Filling Machine



1650 mm

980 mm

OPTIONAL

AISI 304 stainless steel frame
Capacity of bags: 1-28 litri
Maximum bags size: 60x60cm
The work top is adjustable in inclination
Corks are taken off and inserted by hand through a lever
Stainless steel impeller litre-counter
The product volume is set through a display
The air can be sucked up before filling
Azote can be injected after filling
Air evacuation, product filling and azote injection are automatic
Filling time (for a 3-litre bag): 12-14s
The standard machine is as bench version
It is forbidden to use soda for the washing

73 Kg

PNEUMATIC STARTING

Air consumption 6 bar: 8,0 NI/bag

Stainless steel H model wheeled support
Filling pump (the wheeled support is required)
Flexible impeller pump (the wheeled support is required)

ELECTRIC STARTING

230 Volt, 50 Hz mono-phase motor

R900 Filling Machine



1555 mm

525 mm

AISI 304 stainless steel frame
This filling machine works by weight
Suitable for liquids not charged with gas and stiff containers
Maximum weight: 5 Kg
Filling through a flexible impeller pump
The product weight is set through a display
Self-zeroing of the tare on starting
The filling speed is adjustable

ELECTRIC STARTING

230 Volt, 50 Hz mono-phase motor

60 Kg